

## Geberit DuofixBasic element for wall-hung WC, 112 cm, with Delta concealed cistern 12 cm







Application purposes

- · For drywall construction
- · For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For single flush, dual flush or stop-and-go flush
- For floor constructions 0-20 cm

#### Characteristics

- · Self-supporting frame, powder-coated
- · Frame top open
- Frame with ø 9 mm drilling holes for fastening in wood frame construction
- Frame with holes to receive Geberit Duofix wall anchors for elements with frame top open

- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- · Galvanized feet
- Feet adjustable 0–20 cm
- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- · Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- Equipped with conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- With fastening option for electrical connection

#### **Technical data**

| - | Flush volume, factory setting        | 6 and 3 l     |
|---|--------------------------------------|---------------|
|   | Flush volume large, adjustment range | 4.5 / 6 / 7.5 |
|   | Flush volume small, adjustment range | 3-41          |

### Scope of delivery

- Angle stop valve R 1/2", compatible with MF, with adapter ring
- Protection box for service opening, made of polystyrene foam
- · 2 distance bolts
- · Connection set for WC, ø 90 mm
- Connection bend 90° made of PE-HD, ø 90 mm

- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- · Fastening material

| Art. no.     | В     | Н      | Т     |
|--------------|-------|--------|-------|
| 111.153.00.1 | 50 cm | 112 cm | 12 cm |

# Accessories

- Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- Geberit DuofixBasic set of wall anchors for single installation
- Geberit Duofix set of wall anchors for single installation, with crossbar, clip-on



Actuator plate has to be ordered separately