

# Geberit Kombifix element for wall-hung WC, 98 cm, with Omega concealed cistern 12 cm







### **Application purposes**

- · For masonry walls
- · For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- · For dual flush

#### Characteristics

- · Powder-coated installation frame
- · Mounting frame with four fixing brackets
- Adjustable installation depth, 12-20.5 cm
- Fastening for connection bend can be mounted without tools from front
- · Concealed cistern with top or front actuation

- · Concealed cistern, fully insulated against condensation
- · Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- · Water supply connection on the left or rear left
- Protection box for service opening can be cut to length
- Equipped with conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- With fastening option for electrical connection

### **Technical data**

Flow pressure	0.1-10 bar
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4/4.5/6/7.51
Flush volume small, adjustment range	2-41

### Scope of delivery

- Water supply connection Rp 1/2" R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- · Protection box for service opening
- Connection set for WC, ø 90 mm
- · Connection bend made of PE-HD, ø 90 mm

- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- · Fastening material

Art. no.	В	Н	Т
110.011.00.1	42 cm	98 cm	12 cm

## Accessories

- Geberit Kombifix set of leg supports
- Geberit Kombifix set of studs with foot plate



· Actuator plate has to be ordered separately