


## Geberit Sigma concealed cistern 8 cm, 6 / 3 litres



Example image



### Application purposes

- For masonry walls
- For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For floor-standing WCs
- For single flush, dual flush or stop-and-go flush

### Characteristics

- Range 2016
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Premounted direct plastering netting
- Immediate post flush possible with factory setting

### Scope of delivery

- Water supply connection Rp 1/2" - R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Flush bend with recess shells

- Flush bend fitted
- Flush bend adjustable 2 cm upwards and 1 cm downwards
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the top left
- Protection box for service opening can be cut to length, suitable for surface-even actuator plates

### Technical data

Flow pressure	0.1-10 bar
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5 l
Flush volume small, adjustment range	3-4 l

- Flush bend extension,  $\varnothing$  45 mm
- Protection plug
- 2 slotted flat irons
- Fastening material

Art. no.	B	H	T
109.791.00.1	41 cm	62.5 cm	8 cm



- Actuator plate has to be ordered separately